













- DESCRIPTION
- Heavy duty track mounted Crusher with following features:
- CRUSHING CHAMBER
- •Feed opening 914mm (44")
- Crusher speed 672 rpm
- •Crusher Drive Hydraulic Direct drive
- •Min. opening 10mm (3\8") (Fine liner)
- •Max. opening 165mm (1 3\4") (Coarse Liner)
- •Cone weight 14,970kg (33,000 lbs)
- Closed side setting adjustment Hydraulic
- Motor Kawasaki axial piston 800cc/rev
- •Flow rate 608 Lpm (160 US gpm)
- •Level sensor Ultrasonic



POWERUNIT AND HYDRAULICS

- •Engine CAT C13 Tier 4 Interim or Volvo Tier 4 Final
- •Engine power 328 kW (440 HP)
- •Engine speed 1900 rpm
- •Flywheel Pump 1 Kawasaki K5V160DP
- •LH PTO Pump 2 David Brown 5036 5023
- •RH PTO Pump 3 Pump 4045 011
- •Total system flow 798.4 Lpm (211 US Gpm)
- Hydraulic Oil cooler 2 off

•CAPACITIES

- Diesel tank capacity 800 L (211 US gal)
- •Hydraulic tank capacity 1800 L (475 US Gals)



•FEEDER

- •Feeder opening width 800mm (31.5")
- •Feeder belt width 1050mm (42")
- Motor Danfoss OMSS 125
- •Gearbox Bonfig 809W2 23.6:1
- •Flow rate 87.4 Lpm (23.1 US gpm)
- Adjustable speed Yes
- Maximum speed 29 rpm
- •Hopper
- •Length 3780mm (12' 4.9")
- •Width 2200mm (7' 2")
- •Volume 5m3 (6.5yd3")
- Material 6mm sides + 10mm Hardox liners



MAIN CONVEYOR

- •Stockpile height 3250mm (10' 8")
- •Belt width 1050mm (42")
- •Belt spec Plain 500/3 8+2
- Motor OMV630
- •Flow rate 68.4 Lpm (18.1 US gpm)
- •Maximum speed 108.5 rpm
- Angle adjustable YES
- Quick release YES



•ELECTRICS

- Emergency stops 4 off,
- Chassis cabling Armored cable
- Start Siren YES 10 sec delay
- Control panel Plus 1 Danfoss colour screen
- •Engine shutdowns:
 - Low oil pressure
 - High water temp
 - Air filter blockage (selectable)
 - Fuel contamination
 - Low hydraulic tank level
- Engine room light YES
- •Radio control tracks optional Hetronic system
- Pendant track control YES plugged in control cabinet



•OPTIONS

- •Roll-in bogie system
- Main conveyor variable speed control
- Interlock system
- Hopper Extensions
- Water Pump and dust suppression system
- Coarse, Medium or Fine liners
- Work lights
- Belt scale



